



WN

06/ 08/ 10/ 13

CARBIDE INSERTS

WNMA



366

WNMG



366

WNMM



375

CER AND CBN INSERTS

WNGA CBN



376

MATCH THE RIGHT SIZE (example)

Insert

WNMA 080408

Tool Holder


DWLNL 2020 K 08

ISO TURNING – EXTERNAL

DWLNL(RL) EXT

95°

WN..

06
08
10
1316×16
40×40

377

366 – 376


MWLNL(RL) EXT

95°

WN..



08

25×25
40×40


379

366 – 376

PWLNL(RL) EXT

95°

WN..

06
0816×16
32×25


380

366 – 376

C.-DWLNL(RL) EXT

95°

WN..

06
08C4
C6

381


366 – 376

ISO TURNING – INTERNAL

DWLNL(RL) INT

95°

WN..

06
0832
63


382

366 – 376

PWLNL(RL) INT

95°

WN..

06
0820
80


383

366 – 376

C.-DWLNL(RL) INT

95°

WN..

06
0827
33

385


366 – 376



WNMA




	IC	D1	L	S
	[mm]	[mm]	[mm]	[mm]
0804	12.700	5.16	8.70	4.76




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product	RE	P			M			K			N			S			H		
		vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]



For fine-finish to semi-rough machining, and continuous to slightly interrupted cuts.

WNMA 080404	T5305	0.4	—	—	—	—	—	—	235	0.10	4.0	—	—	—	—	—	—	50	0.15	1.0
	T5315	0.4	—	—	—	—	—	—	200	0.10	4.0	—	—	—	—	—	—	40	0.15	1.0
WNMA 080408	T5305	0.8	—	—	—	—	—	—	220	0.20	4.0	—	—	—	—	—	—	45	0.15	1.0
	T5315	0.8	—	—	—	—	—	—	190	0.20	4.0	—	—	—	—	—	—	40	0.15	1.0
	T6310	0.8	—	—	—	—	—	—	100	0.20	4.0	—	—	—	—	—	—	25	0.15	1.0
WNMA 080412	T5305	1.2	—	—	—	—	—	—	195	0.30	4.0	—	—	—	—	—	—	40	0.15	1.0
	T5315	1.2	—	—	—	—	—	—	180	0.30	4.0	—	—	—	—	—	—	35	0.15	1.0
	T6310	1.2	—	—	—	—	—	—	95	0.30	4.0	—	—	—	—	—	—	20	0.15	1.0




For fine-finish to semi-rough machining and continuous to slightly interrupted cuts.

WNMA 080408S	T5305	0.8	—	—	—	—	—	—	220	0.20	4.0	—	—	—	—	—	—	45	0.15	1.0
--------------	-------	-----	---	---	---	---	---	---	-----	------	-----	---	---	---	---	---	---	----	------	-----

WNMG




	IC	D1	L	S
	[mm]	[mm]	[mm]	[mm]
0604	9.525	3.81	6.50	4.76
06T3	9.525	3.81	6.50	3.97
0804	12.700	5.16	8.70	4.76



Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product	RE	P			M			K			N			S			H		
		vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]



FF geometry with highly positive design for fine-finish machining, and continuous to slightly interrupted cuts.



WNMG 060402E-FF	T8315	0.2	215	0.10	1.0	125	0.09	1.0	200	0.10	1.0	—	—	—	—	—	—	—	—
WNMG 060404E-FF	T8315	0.4	220	0.12	1.0	130	0.11	1.0	205	0.12	1.0	—	—	—	—	—	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE (mm)	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]



FF geometry with highly positive design for fine-finish machining, and continuous to slightly interrupted cuts.

WNMG 080404E-FF	T7325	0.4	235	0.12	1.0	180	0.11	1.0	—	—	—	—	—	—	—	—	—	—	—	—
	T8315	0.4	220	0.12	1.0	130	0.11	1.0	205	0.12	1.0	—	—	—	—	—	—	—	—	—
WNMG 080408E-FF	T7325	0.8	265	0.15	1.0	205	0.14	1.0	—	—	—	—	—	—	—	—	—	—	—	—
	T8315	0.8	245	0.15	1.0	145	0.14	1.0	230	0.15	1.0	—	—	—	—	—	—	—	—	—



FM geometry with positive design for finish to semi-rough machining, and continuous to slightly interrupted cuts.


WNMG 060404E-FM	T7325	0.4	195	0.20	1.4	150	0.18	1.4	—	—	—	—	—	—	60	0.16	1.1	—	—	—
	T8315	0.4	180	0.20	1.4	105	0.18	1.4	170	0.20	1.4	—	—	—	45	0.14	1.1	—	—	—
	T8330	0.4	175	0.20	1.4	105	0.18	1.4	165	0.20	1.4	—	—	—	40	0.14	1.1	—	—	—
	T8430	0.4	195	0.20	1.4	105	0.18	1.4	160	0.20	1.4	—	—	—	40	0.14	1.1	—	—	—
	T9315	0.4	265	0.20	1.4	—	—	—	250	0.20	1.4	—	—	—	—	—	—	—	—	—
	T9325	0.4	240	0.20	1.4	140	0.18	1.4	225	0.20	1.4	—	—	—	50	0.16	1.1	—	—	—
	TT310	0.4	275	0.20	1.4	165	0.18	1.4	—	—	—	—	—	—	—	—	—	—	—	—
	T7325	0.8	235	0.20	1.4	180	0.18	1.4	—	—	—	—	—	—	75	0.16	1.1	—	—	—
WNMG 060408E-FM	T8330	0.8	205	0.20	1.4	120	0.18	1.4	190	0.20	1.4	—	—	—	50	0.14	1.1	—	—	—
	T8430	0.8	235	0.20	1.4	125	0.18	1.4	190	0.20	1.4	—	—	—	50	0.14	1.1	—	—	—
	T9315	0.8	315	0.20	1.4	—	—	—	295	0.20	1.4	—	—	—	—	—	—	—	—	—
	T9325	0.8	285	0.20	1.4	170	0.18	1.4	270	0.20	1.4	—	—	—	60	0.16	1.1	—	—	—
	T9315	1.2	300	0.27	1.2	—	—	—	285	0.27	1.2	—	—	—	—	—	—	—	—	—
WNMG 06T304E-FM	T7325	0.4	195	0.20	1.4	150	0.18	1.4	—	—	—	—	—	—	60	0.16	1.1	—	—	—
	T8330	0.4	175	0.20	1.4	105	0.18	1.4	165	0.20	1.4	—	—	—	40	0.14	1.1	—	—	—
	T8430	0.4	195	0.20	1.4	105	0.18	1.4	160	0.20	1.4	—	—	—	40	0.14	1.1	—	—	—
	T9325	0.4	240	0.20	1.4	140	0.18	1.4	225	0.20	1.4	—	—	—	50	0.16	1.1	—	—	—
	T8330	0.8	205	0.20	1.4	120	0.18	1.4	190	0.20	1.4	—	—	—	50	0.14	1.1	—	—	—
WNMG 06T308E-FM	T8430	0.8	235	0.20	1.4	125	0.18	1.4	190	0.20	1.4	—	—	—	50	0.14	1.1	—	—	—
	T9325	0.8	285	0.20	1.4	170	0.18	1.4	270	0.20	1.4	—	—	—	60	0.16	1.1	—	—	—
	T7325	0.4	190	0.20	1.9	145	0.18	1.9	—	—	—	—	—	—	60	0.16	1.5	—	—	—
	T7335	0.4	180	0.20	1.9	140	0.18	1.9	—	—	—	—	—	—	55	0.16	1.5	—	—	—
WNMG 080404E-FM	T8315	0.4	180	0.20	1.9	105	0.18	1.9	170	0.20	1.9	—	—	—	45	0.14	1.5	—	—	—
	T8330	0.4	165	0.20	1.9	95	0.18	1.9	155	0.20	1.9	—	—	—	40	0.14	1.5	—	—	—
	T8430	0.4	190	0.20	1.9	105	0.18	1.9	155	0.20	1.9	—	—	—	40	0.14	1.5	—	—	—
	T9310	0.4	285	0.20	1.9	—	—	—	270	0.20	1.9	—	—	—	—	—	—	—	—	—
	T9315	0.4	270	0.20	1.2	—	—	—	255	0.20	1.2	—	—	—	—	—	—	—	—	—
	T9325	0.4	245	0.20	1.2	145	0.18	1.2	230	0.20	1.2	—	—	—	55	0.16	1.0	—	—	—
	T7325	0.8	225	0.20	1.9	175	0.18	1.9	—	—	—	—	—	—	70	0.16	1.5	—	—	—
	T7335	0.8	215	0.20	1.9	165	0.18	1.9	—	—	—	—	—	—	65	0.16	1.5	—	—	—
WNMG 080408E-FM	T8315	0.8	210	0.20	1.9	125	0.18	1.9	195	0.20	1.9	—	—	—	50	0.16	1.5	—	—	—
	T8330	0.8	195	0.20	1.9	115	0.18	1.9	185	0.20	1.9	—	—	—	45	0.16	1.5	—	—	—
	T8430	0.8	225	0.20	1.9	120	0.18	1.9	185	0.20	1.9	—	—	—	45	0.16	1.5	—	—	—
	T9310	0.8	335	0.20	1.9	—	—	—	315	0.20	1.9	—	—	—	—	—	—	—	—	—
	T9315	0.8	310	0.20	1.9	—	—	—	290	0.20	1.9	—	—	—	—	—	—	—	—	—
	T9325	0.8	280	0.20	1.9	165	0.18	1.9	265	0.20	1.9	—	—	—	60	0.16	1.5	—	—	—
	T7325	1.2	220	0.27	1.9	170	0.24	1.9	—	—	—	—	—	—	70	0.19	1.5	—	—	—
	T7335	1.2	205	0.27	1.9	155	0.24	1.9	—	—	—	—	—	—	65	0.19	1.5	—	—	—
WNMG 080412E-FM	T8330	1.2	190	0.27	1.9	110	0.24	1.9	180	0.27	1.9	—	—	—	45	0.19	1.5	—	—	—
	T8430	1.2	210	0.27	1.9	115	0.24	1.9	175	0.27	1.9	—	—	—	45	0.19	1.5	—	—	—
	T9310	1.2	310	0.27	1.9	—	—	—	290	0.27	1.9	—	—	—	—	—	—	—	—	—
	T9315	1.2	285	0.27	1.9	—	—	—	270	0.27	1.9	—	—	—	—	—	—	—	—	—
	T9325	1.2	255	0.27	1.9	150	0.24	1.9	240	0.27	1.9	—	—	—	55	0.19	1.5	—	—	—
	T9325	1.2	255	0.27	1.9	150	0.24	1.9	240	0.27	1.9	—	—	—	55	0.19	1.5	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE (mm)	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]




KR geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMG 080408E-KR	T5305	0.8	255	0.35	3.5	—	—	—	240	0.35	3.5	—	—	—	—	—	—	50	0.15	1.0
	T5315	0.8	230	0.35	3.5	—	—	—	215	0.35	3.5	—	—	—	—	—	—	45	0.15	1.0
WNMG 080412E-KR	T5305	1.2	260	0.40	3.5	—	—	—	245	0.40	3.5	—	—	—	—	—	—	50	0.15	1.0
	T5315	1.2	235	0.40	3.5	—	—	—	220	0.40	3.5	—	—	—	—	—	—	45	0.15	1.0



M geometry for finish to semi-rough machining, and continuous to interrupted cuts.

WNMG 060404E-M	T5315	0.4	250	0.20	1.8	—	—	—	235	0.20	1.8	—	—	—	—	—	—	50	0.15	1.0
	T9315	0.4	240	0.20	1.8	—	—	—	225	0.20	1.8	—	—	—	—	—	—	45	0.15	1.0
	T9325	0.4	215	0.20	1.8	—	—	—	200	0.20	1.8	—	—	—	—	—	—	—	—	—
	T9335	0.4	180	0.20	1.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 060408E-M	T5315	0.8	255	0.32	1.8	—	—	—	240	0.32	1.8	—	—	—	—	—	—	50	0.15	1.0
	T9310	0.8	250	0.32	1.8	—	—	—	235	0.32	1.8	—	—	—	—	—	—	50	0.15	1.0
	T9315	0.8	230	0.32	1.8	—	—	—	215	0.32	1.8	—	—	—	—	—	—	45	0.15	1.0
	T9325	0.8	205	0.32	1.8	—	—	—	190	0.32	1.8	—	—	—	—	—	—	—	—	—
	T9335	0.8	180	0.32	1.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080404E-M	T5315	0.4	260	0.20	1.2	—	—	—	245	0.20	1.2	—	—	—	—	—	—	50	0.15	1.0
	T9315	0.4	235	0.20	2.1	—	—	—	220	0.20	2.1	—	—	—	—	—	—	45	0.15	1.0
	T9325	0.4	210	0.20	2.1	—	—	—	195	0.20	2.1	—	—	—	—	—	—	—	—	—
	T9335	0.4	180	0.20	2.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080408E-M	T5305	0.8	280	0.32	2.1	—	—	—	265	0.32	2.1	—	—	—	—	—	—	55	0.15	1.0
	T5315	0.8	250	0.32	2.1	—	—	—	235	0.32	2.1	—	—	—	—	—	—	50	0.15	1.0
	T8330	0.8	155	0.32	2.1	—	—	—	145	0.32	2.1	—	—	—	—	—	—	30	0.15	1.0
	T8430	0.8	170	0.32	2.1	—	—	—	135	0.32	2.1	—	—	—	—	—	—	25	0.15	1.0
	T9310	0.8	245	0.32	2.1	—	—	—	230	0.32	2.1	—	—	—	—	—	—	45	0.15	1.0
	T9315	0.8	225	0.32	2.1	—	—	—	210	0.32	2.1	—	—	—	—	—	—	45	0.15	1.0
	T9325	0.8	200	0.32	2.1	—	—	—	190	0.32	2.1	—	—	—	—	—	—	—	—	—
	T9335	0.8	180	0.32	2.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080412E-M	T5305	1.2	275	0.40	2.1	—	—	—	260	0.40	2.1	—	—	—	—	—	—	55	0.15	1.0
	T5315	1.2	245	0.40	2.1	—	—	—	230	0.40	2.1	—	—	—	—	—	—	45	0.15	1.0
	T9310	1.2	235	0.40	2.1	—	—	—	220	0.40	2.1	—	—	—	—	—	—	45	0.15	1.0
	T9315	1.2	220	0.40	2.1	—	—	—	205	0.40	2.1	—	—	—	—	—	—	40	0.15	1.0
	T9325	1.2	195	0.40	2.1	—	—	—	185	0.40	2.1	—	—	—	—	—	—	—	—	—
	T9335	1.2	170	0.40	2.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—



NF geometry with highly positive design for fine-finish to medium machining, and continuous cuts.


WNMG 060404E-NF	T6310	0.4	190	0.17	0.8	135	0.15	0.8	150	0.17	0.8	570	0.20	0.8	55	0.12	0.6	—	—	—
	T7325	0.4	215	0.18	0.8	165	0.16	0.8	—	—	—	—	—	—	65	0.16	0.6	—	—	—
	T7335	0.4	210	0.18	0.8	160	0.16	0.8	—	—	—	—	—	—	65	0.16	0.6	—	—	—
	T8315	0.4	200	0.17	0.8	120	0.15	0.8	190	0.17	0.8	600	0.20	0.8	50	0.12	0.6	—	—	—
	T8330	0.4	190	0.17	0.8	110	0.15	0.8	180	0.17	0.8	570	0.20	0.8	45	0.12	0.6	—	—	—
	T8430	0.4	225	0.17	0.8	120	0.15	0.8	185	0.17	0.8	615	0.20	0.8	45	0.12	0.6	—	—	—
	T9315	0.4	305	0.17	0.8	—	—	—	285	0.17	0.8	—	—	—	—	—	—	—	—	—
	T9325	0.4	265	0.18	0.8	155	0.16	0.8	250	0.18	0.8	—	—	—	55	0.16	0.6	—	—	—
WNMG 060408E-NF	T6310	0.8	215	0.19	1.0	150	0.17	1.0	170	0.19	1.0	645	0.23	1.0	60	0.15	0.8	—	—	—
	T7325	0.8	245	0.19	1.0	190	0.17	1.0	—	—	—	—	—	—	75	0.15	0.8	—	—	—
	T8330	0.8	215	0.19	1.0	125	0.17	1.0	200	0.19	1.0	645	0.23	1.0	50	0.15	0.8	—	—	—
	T8430	0.8	245	0.19	1.0	135	0.17	1.0	200	0.19	1.0	675	0.23	1.0	50	0.15	0.8	—	—	—
	T9315	0.8	335	0.19	1.0	—	—	—	315	0.19	1.0	—	—	—	—	—	—	—	—	—
	T9325	0.8	300	0.19	1.0	180	0.17	1.0	285	0.19	1.0	—	—	—	65	0.15	0.8	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE (mm)	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]



NF geometry with highly positive design for fine-finish to medium machining, and continuous cuts.

WNMG 080404E-NF	HF7	0.4	—	—	—	95	0.15	1.7	155	0.17	1.7	495	0.20	1.7	—	—	—	—	—	—
	T6310	0.4	180	0.17	1.7	125	0.15	1.7	145	0.17	1.7	540	0.20	1.7	50	0.14	1.4	—	—	—
	T7325	0.4	200	0.18	1.7	155	0.16	1.7	—	—	—	—	—	—	65	0.16	1.4	—	—	—
	T7335	0.4	195	0.18	1.7	150	0.16	1.7	—	—	—	—	—	—	60	0.16	1.4	—	—	—
	T8315	0.4	185	0.17	1.7	110	0.15	1.7	175	0.17	1.7	555	0.20	1.7	45	0.14	1.4	—	—	—
	T8330	0.4	180	0.17	1.7	105	0.15	1.7	170	0.17	1.7	540	0.20	1.7	45	0.14	1.4	—	—	—
	T8430	0.4	200	0.17	1.7	110	0.15	1.7	165	0.17	1.7	555	0.20	1.7	40	0.14	1.4	—	—	—
	T9315	0.4	285	0.17	1.7	—	—	—	270	0.17	1.7	—	—	—	—	—	—	—	—	—
	T9325	0.4	250	0.18	1.7	150	0.16	1.7	235	0.18	1.7	—	—	—	55	0.16	1.4	—	—	—
WNMG 080408E-NF	HF7	0.8	—	—	—	110	0.17	1.7	180	0.19	1.7	570	0.23	1.7	—	—	—	—	—	—
	T6310	0.8	200	0.19	1.7	140	0.17	1.7	160	0.19	1.7	600	0.23	1.7	60	0.15	1.4	—	—	—
	T7325	0.8	235	0.19	1.7	180	0.17	1.7	—	—	—	—	—	—	75	0.15	1.4	—	—	—
	T7335	0.8	225	0.19	1.7	175	0.17	1.7	—	—	—	—	—	—	70	0.15	1.4	—	—	—
	T8315	0.8	215	0.19	1.7	125	0.17	1.7	200	0.19	1.7	645	0.23	1.7	50	0.15	1.4	—	—	—
	T8330	0.8	200	0.19	1.7	120	0.17	1.7	190	0.19	1.7	600	0.23	1.7	50	0.15	1.4	—	—	—
	T8430	0.8	235	0.19	1.7	125	0.17	1.7	190	0.19	1.7	645	0.23	1.7	50	0.15	1.4	—	—	—
	T9315	0.8	320	0.19	1.7	—	—	—	300	0.19	1.7	—	—	—	—	—	—	—	—	—
	T9325	0.8	285	0.19	1.7	170	0.17	1.7	270	0.19	1.7	—	—	—	60	0.15	1.4	—	—	—
WNMG 080412E-NF	T6310	1.2	185	0.30	2.1	130	0.27	2.1	145	0.30	2.1	555	0.36	2.1	55	0.21	1.7	—	—	—
	T7325	1.2	205	0.30	2.1	155	0.27	2.1	—	—	—	—	—	—	65	0.21	1.7	—	—	—
	T8430	1.2	200	0.30	2.1	110	0.27	2.1	165	0.30	2.1	555	0.36	2.1	40	0.21	1.7	—	—	—
	T9315	1.2	275	0.30	2.1	—	—	—	260	0.30	2.1	—	—	—	—	—	—	—	—	—
	T9325	1.2	245	0.30	2.1	145	0.27	2.1	230	0.30	2.1	—	—	—	55	0.21	1.7	—	—	—



NM geometry with highly positive design for fine-finish, medium and rough machining, with continuous cuts.


WNMG 060404E-NM	T7325	0.4	200	0.20	1.8	155	0.18	1.8	—	—	—	—	—	—	65	0.16	1.4	—	—	—
	T7335	0.4	195	0.20	1.8	150	0.18	1.8	—	—	—	—	—	—	60	0.16	1.4	—	—	—
	T8315	0.4	185	0.20	1.8	110	0.18	1.8	—	—	—	555	0.24	1.8	45	0.16	1.4	—	—	—
	T8330	0.4	175	0.20	1.8	105	0.18	1.8	—	—	—	525	0.24	1.8	40	0.16	1.4	—	—	—
	T8430	0.4	185	0.25	1.8	100	0.23	1.8	—	—	—	510	0.30	1.8	40	0.20	1.4	—	—	—
	T9325	0.4	245	0.20	1.8	145	0.18	1.8	—	—	—	—	—	—	55	0.16	1.4	—	—	—
WNMG 060408E-NM	T7325	0.8	220	0.25	1.8	170	0.23	1.8	—	—	—	—	—	—	70	0.20	1.4	—	—	—
	T7335	0.8	215	0.25	1.8	165	0.23	1.8	—	—	—	—	—	—	65	0.20	1.4	—	—	—
	T8315	0.8	205	0.25	1.8	120	0.23	1.8	—	—	—	615	0.30	1.8	50	0.20	1.4	—	—	—
	T8330	0.8	195	0.25	1.8	115	0.23	1.8	—	—	—	585	0.30	1.8	45	0.20	1.4	—	—	—
	T8430	0.8	220	0.25	1.8	120	0.23	1.8	—	—	—	600	0.30	1.8	45	0.20	1.4	—	—	—
	T9315	0.8	290	0.25	1.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 060412E-NM	T9325	0.8	265	0.25	1.8	155	0.23	1.8	—	—	—	—	—	—	55	0.20	1.4	—	—	—
	T7325	1.2	220	0.30	1.8	170	0.27	1.8	—	—	—	—	—	—	70	0.24	1.4	—	—	—
	T7335	1.2	220	0.30	1.2	170	0.27	1.2	—	—	—	—	—	—	70	0.24	1.0	—	—	—
	T9315	1.2	285	0.30	1.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080404E-NM	T9325	1.2	255	0.30	1.8	150	0.27	1.8	—	—	—	—	—	—	55	0.24	1.4	—	—	—
	T7325	0.4	195	0.20	2.1	150	0.18	2.1	—	—	—	—	—	—	60	0.16	1.7	—	—	—
	T7335	0.4	190	0.20	2.1	145	0.18	2.1	—	—	—	—	—	—	60	0.16	1.7	—	—	—
	T8315	0.4	180	0.20	2.1	105	0.18	2.1	—	—	—	540	0.24	2.1	45	0.16	1.7	—	—	—
	T8330	0.4	170	0.20	2.1	100	0.18	2.1	—	—	—	510	0.24	2.1	40	0.16	1.7	—	—	—
	T8430	0.4	180	0.25	2.1	95	0.23	2.1	—	—	—	495	0.30	2.1	35	0.20	1.7	—	—	—
	T9315	0.4	270	0.20	2.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	0.4	240	0.20	2.1	140	0.18	2.1	—	—	—	—	—	—	50	0.16	1.7	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE (mm)	P			M			K			N			S			H		
			vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)




NM geometry with highly positive design for fine-finish, medium and rough machining, with continuous cuts.

WNMG 080408E-NM	T7325	0.8	215	0.25	2.1	165	0.23	2.1	—	—	—	—	—	—	65	0.20	1.7	—	—	—
	T7335	0.8	210	0.25	2.1	160	0.23	2.1	—	—	—	—	—	—	65	0.20	1.7	—	—	—
	T8315	0.8	205	0.25	2.1	120	0.23	2.1	—	—	—	615	0.30	2.1	50	0.20	1.7	—	—	—
	T8330	0.8	195	0.25	2.1	115	0.23	2.1	—	—	—	585	0.30	2.1	45	0.20	1.7	—	—	—
	T8430	0.8	210	0.25	2.1	115	0.23	2.1	—	—	—	585	0.30	2.1	45	0.20	1.7	—	—	—
	T9315	0.8	290	0.25	2.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	0.8	260	0.25	2.1	155	0.23	2.1	—	—	—	—	—	—	55	0.20	1.7	—	—	—
WNMG 080412E-NM	T7325	1.2	215	0.30	2.1	165	0.27	2.1	—	—	—	—	—	—	65	0.24	1.7	—	—	—
	T7335	1.2	210	0.30	2.1	160	0.27	2.1	—	—	—	—	—	—	65	0.24	1.7	—	—	—
	T8315	1.2	205	0.30	2.1	120	0.27	2.1	—	—	—	615	0.36	2.1	50	0.24	1.7	—	—	—
	T9325	1.2	255	0.30	2.1	150	0.27	2.1	—	—	—	—	—	—	55	0.24	1.7	—	—	—



NMR geometry with positive design for medium to rough machining, and continuous cuts.

WNMG 060404E-NMR	T6310	0.4	145	0.25	1.6	100	0.23	1.6	—	—	—	—	—	—	40	0.20	1.3	—	—	—
	T7325	0.4	160	0.25	1.6	120	0.23	1.6	—	—	—	—	—	—	50	0.20	1.3	—	—	—
	T8430	0.4	145	0.31	1.6	80	0.28	1.6	—	—	—	—	—	—	30	0.25	1.3	—	—	—
	T9325	0.4	200	0.25	1.6	120	0.23	1.6	—	—	—	—	—	—	45	0.20	1.3	—	—	—
WNMG 060408E-NMR	T6310	0.8	155	0.35	1.6	110	0.32	1.6	—	—	—	—	—	—	45	0.25	1.3	—	—	—
	T7325	0.8	175	0.35	1.6	135	0.32	1.6	—	—	—	—	—	—	55	0.25	1.3	—	—	—
	T7335	0.8	170	0.35	1.6	130	0.32	1.6	—	—	—	—	—	—	55	0.25	1.3	—	—	—
	T9315	0.8	225	0.35	1.6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	0.8	200	0.35	1.6	120	0.32	1.6	—	—	—	—	—	—	45	0.25	1.3	—	—	—
WNMG 080404E-NMR	T6310	0.4	140	0.25	2.7	100	0.23	2.7	—	—	—	—	—	—	40	0.20	2.2	—	—	—
	T7325	0.4	155	0.25	2.7	120	0.23	2.7	—	—	—	—	—	—	50	0.20	2.2	—	—	—
	T7335	0.4	150	0.25	2.7	115	0.23	2.7	—	—	—	—	—	—	45	0.20	2.2	—	—	—
	T8330	0.4	140	0.25	2.7	80	0.23	2.7	—	—	—	—	—	—	35	0.20	2.2	—	—	—
	T8430	0.4	140	0.31	2.7	75	0.28	2.7	—	—	—	—	—	—	30	0.25	2.2	—	—	—
	T9315	0.4	205	0.25	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	0.4	185	0.25	2.7	110	0.23	2.7	—	—	—	—	—	—	40	0.20	2.2	—	—	—
WNMG 080408E-NMR	T6310	0.8	150	0.35	2.7	105	0.32	2.7	—	—	—	—	—	—	45	0.25	2.2	—	—	—
	T7325	0.8	170	0.35	2.7	130	0.32	2.7	—	—	—	—	—	—	55	0.25	2.2	—	—	—
	T7335	0.8	160	0.35	2.7	120	0.32	2.7	—	—	—	—	—	—	50	0.25	2.2	—	—	—
	T8330	0.8	150	0.35	2.7	90	0.32	2.7	—	—	—	—	—	—	35	0.25	2.2	—	—	—
	T8430	0.8	155	0.35	2.7	85	0.32	2.7	—	—	—	—	—	—	30	0.25	2.2	—	—	—
	T9315	0.8	210	0.35	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	0.8	190	0.35	2.7	110	0.32	2.7	—	—	—	—	—	—	40	0.25	2.2	—	—	—
	T9325	0.8	190	0.35	2.7	110	0.32	2.7	—	—	—	—	—	—	40	0.25	2.2	—	—	—
WNMG 080412E-NMR	T6310	1.2	150	0.40	2.7	105	0.36	2.7	—	—	—	—	—	—	45	0.28	2.2	—	—	—
	T7325	1.2	170	0.40	2.7	130	0.36	2.7	—	—	—	—	—	—	55	0.28	2.2	—	—	—
	T7335	1.2	160	0.40	2.7	120	0.36	2.7	—	—	—	—	—	—	50	0.28	2.2	—	—	—
	T8330	1.2	150	0.40	2.7	90	0.36	2.7	—	—	—	—	—	—	35	0.28	2.2	—	—	—
	T8430	1.2	155	0.40	2.7	85	0.36	2.7	—	—	—	—	—	—	30	0.28	2.2	—	—	—
	T9315	1.2	215	0.40	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	T9325	1.2	190	0.40	2.7	110	0.36	2.7	—	—	—	—	—	—	40	0.28	2.2	—	—	—



NRM geometry with positive design for semi-rough to rough machining, and continuous to moderate interrupted cuts.



WNMG 080404-NRM	T7325	0.4	155	0.25	2.7	120	0.23	2.7	—	—	—	—	—	—	50	0.18	2.2	—	—	—
	T7335	0.4	150	0.25	2.7	115	0.23	2.7	—	—	—	—	—	—	45	0.18	2.2	—	—	—
	T9315	0.4	205	0.25	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080408-NRM	T7325	0.8	170	0.35	2.7	130	0.32	2.7	—	—	—	—	—	—	55	0.28	2.2	—	—	—
	T7335	0.8	160	0.35	2.7	120	0.32	2.7	—	—	—	—	—	—	50	0.28	2.2	—	—	—
	T9315	0.8	210	0.35	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE (mm)	P			M			K			N			S			H		
			vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]





NRM geometry with positive design for semi-rough to rough machining, and continuous to moderate interrupted cuts.

WNMG 080412-NRM	T7325	1.2	170	0.40	2.7	130	0.36	2.7	—	—	—	—	—	—	55	0.28	2.2	—	—	—
	T7335	1.2	160	0.40	2.7	120	0.36	2.7	—	—	—	—	—	—	50	0.28	2.2	—	—	—
	T9315	1.2	215	0.40	2.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—



R geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMG 080408E-R	T5305	0.8	245	0.40	3.5	—	—	—	230	0.40	3.5	—	—	—	—	—	—	45	0.15	1.0
	T5315	0.8	220	0.40	3.5	—	—	—	205	0.40	3.5	—	—	—	—	—	—	40	0.15	1.0
	T9310	0.8	210	0.40	3.5	—	—	—	195	0.40	3.5	—	—	—	—	—	—	40	0.15	1.0
	T9315	0.8	195	0.40	3.5	—	—	—	185	0.40	3.5	—	—	—	—	—	—	35	0.15	1.0
	T9325	0.8	175	0.40	3.5	—	—	—	165	0.40	3.5	—	—	—	—	—	—	—	—	—
	T9335	0.8	155	0.40	3.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
WNMG 080412E-R	T5305	1.2	250	0.45	3.5	—	—	—	235	0.45	3.5	—	—	—	—	—	—	50	0.15	1.0
	T5315	1.2	225	0.45	3.5	—	—	—	210	0.45	3.5	—	—	—	—	—	—	45	0.15	1.0
	T9310	1.2	215	0.45	3.5	—	—	—	200	0.45	3.5	—	—	—	—	—	—	40	0.15	1.0
	T9315	1.2	200	0.45	3.5	—	—	—	190	0.45	3.5	—	—	—	—	—	—	40	0.15	1.0
	T9325	1.2	180	0.45	3.5	—	—	—	170	0.45	3.5	—	—	—	—	—	—	—	—	—
	T9335	1.2	155	0.45	3.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—



RM geometry for semi-rough to rough machining, and continuous to interrupted cuts.


WNMG 060412E-RM	T9310	1.2	245	0.45	3.0	—	—	—	230	0.45	3.0	—	—	—	—	—	—
	T9315	1.2	230	0.45	3.0	—	—	—	215	0.45	3.0	—	—	—	—	—	—
	T9325	1.2	230	0.45	1.2	135	0.41	1.2	215	0.45	1.2	—	—	—	—	—	—
WNMG 080408E-RM	T5305	0.8	275	0.40	4.0	—	—	—	260	0.40	4.0	—	—	—	—	—	—
	T5315	0.8	250	0.40	4.0	—	—	—	235	0.40	4.0	—	—	—	—	—	—
	T7325	0.8	180	0.40	4.0	140	0.36	4.0	—	—	—	—	—	—	—	—	—
	T7335	0.8	165	0.40	4.0	125	0.36	4.0	—	—	—	—	—	—	—	—	—
	T8315	0.8	165	0.40	4.0	95	0.36	4.0	155	0.40	4.0	—	—	—	—	—	—
	T8330	0.8	155	0.40	4.0	90	0.36	4.0	145	0.40	4.0	—	—	—	—	—	—
	T8430	0.8	165	0.40	4.0	90	0.36	4.0	135	0.40	4.0	—	—	—	—	—	—
	T9310	0.8	240	0.40	4.0	—	—	—	225	0.40	4.0	—	—	—	—	—	—
	T9315	0.8	220	0.40	4.0	—	—	—	205	0.40	4.0	—	—	—	—	—	—
	T9325	0.8	200	0.40	4.0	120	0.36	4.0	190	0.40	4.0	—	—	—	—	—	—
	T9335	0.8	170	0.40	4.0	100	0.36	4.0	—	—	—	—	—	—	—	—	—
	WNMG 080412E-RM	T5305	1.2	280	0.45	4.0	—	—	—	265	0.45	4.0	—	—	—	—	—
T5315		1.2	250	0.45	4.0	—	—	—	235	0.45	4.0	—	—	—	—	—	—
T7325		1.2	180	0.45	4.0	140	0.41	4.0	—	—	—	—	—	—	—	—	—
T7335		1.2	170	0.45	4.0	130	0.41	4.0	—	—	—	—	—	—	—	—	—
T8315		1.2	170	0.45	4.0	100	0.41	4.0	160	0.45	4.0	—	—	—	—	—	—
T9310		1.2	240	0.45	4.0	—	—	—	225	0.45	4.0	—	—	—	—	—	—
T9315		1.2	220	0.45	4.0	—	—	—	205	0.45	4.0	—	—	—	—	—	—
T9325		1.2	200	0.45	4.0	120	0.41	4.0	190	0.45	4.0	—	—	—	—	—	—
T9335		1.2	175	0.45	4.0	105	0.41	4.0	—	—	—	—	—	—	—	—	—
WNMG 080416E-RM		T5305	1.6	280	0.50	4.0	—	—	—	265	0.50	4.0	—	—	—	—	—
	T5315	1.6	255	0.50	4.0	—	—	—	240	0.50	4.0	—	—	—	—	—	—
	T7335	1.6	175	0.50	4.0	135	0.45	4.0	—	—	—	—	—	—	—	—	—
	T8430	1.6	170	0.50	4.0	90	0.45	4.0	135	0.50	4.0	—	—	—	—	—	—
	T9310	1.6	240	0.50	4.0	—	—	—	225	0.50	4.0	—	—	—	—	—	—
	T9315	1.6	220	0.50	4.0	—	—	—	205	0.50	4.0	—	—	—	—	—	—
	T9325	1.6	205	0.50	4.0	120	0.45	4.0	190	0.50	4.0	—	—	—	—	—	—
	T9335	1.6	175	0.50	4.0	105	0.45	4.0	—	—	—	—	—	—	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product	RE  (mm)	P			M			K			N			S			H		
		vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
		[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]



SF geometry with positive design for fine-finish machining and for machining thin walls, with continuous cuts.

WNMG 060404E-SF	H07	0.4	—	—	—	90	0.14	1.0	145	0.15	1.0	470	0.18	1.0	45	0.12	0.8	—	—	—
	T6310	0.4	180	0.15	1.0	125	0.14	1.0	145	0.15	1.0	540	0.18	1.0	50	0.12	0.8	35	0.15	1.0
	T7325	0.4	205	0.17	1.0	155	0.15	1.0	—	—	—	—	—	—	65	0.15	0.8	—	—	—
	T7335	0.4	200	0.17	1.0	155	0.15	1.0	—	—	—	—	—	—	65	0.15	0.8	—	—	—
	T8315	0.4	195	0.15	1.0	115	0.14	1.0	185	0.15	1.0	585	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T8330	0.4	180	0.15	1.0	105	0.14	1.0	170	0.15	1.0	540	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T8430	0.4	220	0.15	1.0	120	0.14	1.0	180	0.15	1.0	600	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T9325	0.4	255	0.17	1.0	150	0.15	1.0	240	0.17	1.0	—	—	—	55	0.15	0.8	—	—	—
	T9315	0.8	—	—	—	95	0.18	1.0	155	0.20	1.0	495	0.24	1.0	50	0.14	0.8	—	—	—
WNMG 060408E-SF	H07	0.8	—	—	—	95	0.18	1.0	155	0.20	1.0	495	0.24	1.0	50	0.14	0.8	—	—	—
	T6310	0.8	200	0.20	1.0	140	0.18	1.0	160	0.20	1.0	600	0.24	1.0	60	0.14	0.8	40	0.15	1.0
	T7325	0.8	220	0.20	1.0	170	0.18	1.0	—	—	—	—	—	—	70	0.16	0.8	—	—	—
	T7335	0.8	220	0.20	1.0	170	0.18	1.0	—	—	—	—	—	—	70	0.16	0.8	—	—	—
	T8315	0.8	210	0.20	1.0	125	0.18	1.0	195	0.20	1.0	630	0.24	1.0	50	0.14	0.8	40	0.15	1.0
	T8330	0.8	200	0.20	1.0	120	0.18	1.0	190	0.20	1.0	600	0.24	1.0	50	0.14	0.8	40	0.15	1.0
	T8430	0.8	230	0.20	1.0	125	0.18	1.0	185	0.20	1.0	630	0.24	1.0	45	0.14	0.8	35	0.15	1.0
	T9315	0.8	315	0.20	1.0	—	—	—	295	0.20	1.0	—	—	—	—	—	—	60	0.15	1.0
	T9325	0.8	280	0.20	1.0	165	0.18	1.0	265	0.20	1.0	—	—	—	60	0.16	0.8	—	—	—
WNMG 080404E-SF	H07	0.4	—	—	—	90	0.14	1.0	145	0.15	1.0	470	0.18	1.0	45	0.12	0.8	—	—	—
	T6310	0.4	180	0.15	1.0	125	0.14	1.0	145	0.15	1.0	540	0.18	1.0	50	0.12	0.8	35	0.15	1.0
	T7325	0.4	205	0.17	1.0	155	0.15	1.0	—	—	—	—	—	—	65	0.15	0.8	—	—	—
	T7335	0.4	200	0.17	1.0	155	0.15	1.0	—	—	—	—	—	—	65	0.15	0.8	—	—	—
	T8315	0.4	195	0.15	1.0	115	0.14	1.0	185	0.15	1.0	585	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T8330	0.4	180	0.15	1.0	105	0.14	1.0	170	0.15	1.0	540	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T8430	0.4	220	0.15	1.0	120	0.14	1.0	180	0.15	1.0	600	0.18	1.0	45	0.12	0.8	35	0.15	1.0
	T9315	0.4	300	0.15	1.0	—	—	—	285	0.15	1.0	—	—	—	—	—	—	60	0.15	1.0
	T9325	0.4	255	0.17	1.0	150	0.15	1.0	240	0.17	1.0	—	—	—	55	0.15	0.8	—	—	—
WNMG 080408E-SF	H07	0.8	—	—	—	95	0.18	1.0	155	0.20	1.0	495	0.24	1.0	50	0.14	0.8	—	—	—
	T6310	0.8	200	0.20	1.0	140	0.18	1.0	160	0.20	1.0	600	0.24	1.0	60	0.14	0.8	40	0.15	1.0
	T7325	0.8	230	0.20	1.0	175	0.18	1.0	—	—	—	—	—	—	70	0.16	0.8	—	—	—
	T7335	0.8	220	0.20	1.0	170	0.18	1.0	—	—	—	—	—	—	70	0.16	0.8	—	—	—
	T8315	0.8	210	0.20	1.0	125	0.18	1.0	195	0.20	1.0	630	0.24	1.0	50	0.14	0.8	40	0.15	1.0
	T8330	0.8	200	0.20	1.0	120	0.18	1.0	190	0.20	1.0	600	0.24	1.0	50	0.14	0.8	40	0.15	1.0
	T8430	0.8	230	0.20	1.0	125	0.18	1.0	185	0.20	1.0	630	0.24	1.0	45	0.14	0.8	35	0.15	1.0
	T9315	0.8	315	0.20	1.0	—	—	—	295	0.20	1.0	—	—	—	—	—	—	60	0.15	1.0
	T9325	0.8	280	0.20	1.0	165	0.18	1.0	265	0.20	1.0	—	—	—	60	0.16	0.8	—	—	—
WNMG 080412E-SF	T7325	1.2	220	0.25	1.5	170	0.23	1.5	—	—	—	—	—	—	70	0.18	1.2	—	—	—



SM geometry with positive design for medium machining, and continuous to interrupted cuts.


WNMG 060404E-SM	T7325	0.4	180	0.22	1.7	140	0.20	1.7	—	—	—	—	—	—	55	0.20	1.4	—	—	—
	T7335	0.4	175	0.22	1.7	135	0.20	1.7	—	—	—	—	—	—	55	0.20	1.4	—	—	—
	T8330	0.4	155	0.22	1.7	90	0.20	1.7	145	0.22	1.7	465	0.26	1.7	35	0.20	1.4	30	0.15	1.0
	T8430	0.4	175	0.22	1.7	95	0.20	1.7	140	0.22	1.7	480	0.26	1.7	35	0.20	1.4	30	0.15	1.0
	T9315	0.4	250	0.20	1.7	—	—	—	235	0.20	1.7	—	—	—	—	—	—	50	0.15	1.0
	T9325	0.4	215	0.22	1.7	125	0.20	1.7	200	0.22	1.7	—	—	—	45	0.20	1.4	—	—	—
WNMG 060408E-SM	T6310	0.8	175	0.25	1.7	125	0.23	1.7	140	0.25	1.7	525	0.30	1.7	50	0.20	1.4	35	0.15	1.0
	T7325	0.8	200	0.25	1.7	155	0.23	1.7	—	—	—	—	—	—	65	0.20	1.4	—	—	—
	T7335	0.8	195	0.25	1.7	150	0.23	1.7	—	—	—	—	—	—	60	0.20	1.4	—	—	—
	T8330	0.8	175	0.25	1.7	105	0.23	1.7	165	0.25	1.7	525	0.30	1.7	40	0.20	1.4	35	0.15	1.0
	T8430	0.8	195	0.25	1.7	105	0.23	1.7	160	0.25	1.7	540	0.30	1.7	40	0.20	1.4	30	0.15	1.0
	T9325	0.8	240	0.25	1.7	140	0.23	1.7	225	0.25	1.7	—	—	—	50	0.20	1.4	—	—	—
WNMG 060412E-SM	T7325	1.2	200	0.30	1.7	155	0.27	1.7	—	—	—	—	—	—	65	0.24	1.4	—	—	—
	T8330	1.2	180	0.30	1.7	105	0.27	1.7	170	0.30	1.7	540	0.36	1.7	45	0.24	1.4	35	0.15	1.0
	T8430	1.2	195	0.30	1.7	105	0.27	1.7	160	0.30	1.7	540	0.36	1.7	40	0.24	1.4	30	0.15	1.0
	T9325	1.2	240	0.30	1.7	140	0.27	1.7	225	0.30	1.7	—	—	—	50	0.24	1.4	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----





Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE [mm]	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]





SM geometry with positive design for medium machining, and continuous to interrupted cuts.

WNMG 080404E-SM	T6310	0.4	■	155	0.22	2.0	■	110	0.20	2.0	■	125	0.22	2.0	■	465	0.26	2.0	■	45	0.20	1.6	■	30	0.15	1.0
	T7325	0.4	■	175	0.22	2.0	■	135	0.20	2.0	■	—	—	—	■	—	—	—	■	55	0.20	1.6	■	—	—	—
	T7335	0.4	■	170	0.22	2.0	■	130	0.20	2.0	■	—	—	—	■	—	—	—	■	55	0.20	1.6	■	—	—	—
	T8330	0.4	■	155	0.22	2.0	■	90	0.20	2.0	■	145	0.22	2.0	■	465	0.26	2.0	■	35	0.20	1.6	■	30	0.15	1.0
	T8430	0.4	■	170	0.22	2.0	■	90	0.20	2.0	■	135	0.22	2.0	■	465	0.26	2.0	■	35	0.20	1.6	■	25	0.15	1.0
	T9315	0.4	■	245	0.20	2.0	■	—	—	—	■	230	0.20	2.0	■	—	—	—	■	—	—	—	■	45	0.15	1.0
	T9325	0.4	■	210	0.22	2.0	■	125	0.20	2.0	■	195	0.22	2.0	■	—	—	—	■	45	0.20	1.6	■	—	—	—
WNMG 080408E-SM	T6310	0.8	■	175	0.25	2.0	■	125	0.23	2.0	■	140	0.25	2.0	■	525	0.30	2.0	■	50	0.20	1.6	■	35	0.15	1.0
	T7325	0.8	■	200	0.25	2.0	■	155	0.23	2.0	■	—	—	—	■	—	—	—	■	65	0.20	1.6	■	—	—	—
	T7335	0.8	■	190	0.25	2.0	■	145	0.23	2.0	■	—	—	—	■	—	—	—	■	60	0.20	1.6	■	—	—	—
	T8330	0.8	■	175	0.25	2.0	■	105	0.23	2.0	■	165	0.25	2.0	■	525	0.30	2.0	■	40	0.20	1.6	■	35	0.15	1.0
	T8430	0.8	■	195	0.25	2.0	■	105	0.23	2.0	■	160	0.25	2.0	■	540	0.30	2.0	■	40	0.20	1.6	■	30	0.15	1.0
	T9315	0.8	■	265	0.25	2.0	■	—	—	—	■	250	0.25	2.0	■	—	—	—	■	—	—	—	■	50	0.15	1.0
	T9325	0.8	■	235	0.25	2.0	■	140	0.23	2.0	■	220	0.25	2.0	■	—	—	—	■	50	0.20	1.6	■	—	—	—
WNMG 080412E-SM	T6310	1.2	■	175	0.30	2.0	■	125	0.27	2.0	■	140	0.30	2.0	■	525	0.36	2.0	■	50	0.24	1.6	■	35	0.15	1.0
	T7325	1.2	■	195	0.30	2.0	■	150	0.27	2.0	■	—	—	—	■	—	—	—	■	60	0.24	1.6	■	—	—	—
	T7335	1.2	■	190	0.30	2.0	■	145	0.27	2.0	■	—	—	—	■	—	—	—	■	60	0.24	1.6	■	—	—	—
	T8330	1.2	■	175	0.30	2.0	■	105	0.27	2.0	■	165	0.30	2.0	■	525	0.36	2.0	■	40	0.24	1.6	■	35	0.15	1.0
	T8430	1.2	■	190	0.30	2.0	■	105	0.27	2.0	■	155	0.30	2.0	■	525	0.36	2.0	■	40	0.24	1.6	■	30	0.15	1.0
	T9315	1.2	■	260	0.30	2.0	■	—	—	—	■	245	0.30	2.0	■	—	—	—	■	—	—	—	■	50	0.15	1.0
	T9325	1.2	■	235	0.30	2.0	■	140	0.27	2.0	■	220	0.30	2.0	■	—	—	—	■	50	0.24	1.6	■	—	—	—



ER-SI geometry with positive right-handed geometry for fine-finish to semi-rough machining, and continuous cuts.

WNMG 060404ER-SI	T8330	0.4	■	195	0.20	1.7	■	115	0.18	1.7	■	—	—	—	■	585	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T8430	0.4	■	225	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T9325	0.4	■	270	0.20	1.7	■	160	0.18	1.7	■	—	—	—	■	—	—	—	■	60	0.18	1.4	■	—	—	—
WNMG 080404ER-SI	T7325	0.4	■	220	0.20	1.7	■	170	0.18	1.7	■	—	—	—	■	—	—	—	■	70	0.18	1.4	■	—	—	—
	T7335	0.4	■	215	0.20	1.7	■	165	0.18	1.7	■	—	—	—	■	—	—	—	■	65	0.18	1.4	■	—	—	—
	T8315	0.4	■	205	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	50	0.18	1.4	■	—	—	—
	T8330	0.4	■	195	0.20	1.7	■	115	0.18	1.7	■	—	—	—	■	585	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T8430	0.4	■	225	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	45	0.18	1.4	■	—	—	—
WNMG 080408ER-SI	T9325	0.4	■	270	0.20	1.7	■	160	0.18	1.7	■	—	—	—	■	—	—	—	■	60	0.18	1.4	■	—	—	—
	T7325	0.8	■	215	0.35	1.7	■	165	0.32	1.7	■	—	—	—	■	—	—	—	■	65	0.25	1.4	■	—	—	—
	T7335	0.8	■	205	0.35	1.7	■	155	0.32	1.7	■	—	—	—	■	—	—	—	■	65	0.25	1.4	■	—	—	—
	T8315	0.8	■	205	0.35	1.7	■	120	0.32	1.7	■	—	—	—	■	615	0.42	1.7	■	50	0.25	1.4	■	—	—	—
	T8330	0.8	■	195	0.35	1.7	■	115	0.32	1.7	■	—	—	—	■	585	0.42	1.7	■	45	0.25	1.4	■	—	—	—
	T8430	0.8	■	210	0.35	1.7	■	115	0.32	1.7	■	—	—	—	■	585	0.42	1.7	■	45	0.25	1.4	■	—	—	—
	T9325	0.8	■	255	0.35	1.7	■	150	0.32	1.7	■	—	—	—	■	—	—	—	■	55	0.25	1.4	■	—	—	—
WNMG 080412ER-SI	T8430	1.2	■	225	0.35	1.7	■	120	0.32	1.7	■	—	—	—	■	615	0.42	1.7	■	45	0.25	1.4	■	—	—	—
	T9325	1.2	■	265	0.35	1.7	■	155	0.32	1.7	■	—	—	—	■	—	—	—	■	55	0.25	1.4	■	—	—	—



EL-SI geometry with positive left-handed design for fine-finish to semi-rough machining, and continuous cuts.



WNMG 060404EL-SI	T8330	0.4	■	195	0.20	1.7	■	115	0.18	1.7	■	—	—	—	■	585	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T8430	0.4	■	225	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T9325	0.4	■	270	0.20	1.7	■	160	0.18	1.7	■	—	—	—	■	—	—	—	■	60	0.18	1.4	■	—	—	—
WNMG 080404EL-SI	T7325	0.4	■	220	0.20	1.7	■	170	0.18	1.7	■	—	—	—	■	—	—	—	■	70	0.18	1.4	■	—	—	—
	T7335	0.4	■	215	0.20	1.7	■	165	0.18	1.7	■	—	—	—	■	—	—	—	■	65	0.18	1.4	■	—	—	—
	T8315	0.4	■	205	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	50	0.18	1.4	■	—	—	—
	T8330	0.4	■	195	0.20	1.7	■	115	0.18	1.7	■	—	—	—	■	585	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T8430	0.4	■	225	0.20	1.7	■	120	0.18	1.7	■	—	—	—	■	615	0.24	1.7	■	45	0.18	1.4	■	—	—	—
	T9325	0.4	■	270	0.20	1.7	■	160	0.18	1.7	■	—	—	—	■	—	—	—	■	60	0.18	1.4	■	—	—	—

CN	DN	KN	LN	RN	SN	TN	VN	WN
----	----	----	----	----	----	----	----	----




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product	RE  (mm)	P			M			K			N			S			H		
		vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)	vc (m/min)	f (mm/rev)	ap (mm)




EL-SI geometry with positive left-handed design for fine-finish to semi-rough machining, and continuous cuts.

WNMG 080408EL-SI	T7325	0.8	215	0.35	1.7	165	0.32	1.7	—	—	—	—	—	—	65	0.25	1.4	—	—	—
	T7335	0.8	205	0.35	1.7	155	0.32	1.7	—	—	—	—	—	—	65	0.25	1.4	—	—	—
	T8315	0.8	205	0.35	1.7	120	0.32	1.7	—	—	—	615	0.42	1.7	50	0.25	1.4	—	—	—
	T8330	0.8	195	0.35	1.7	115	0.32	1.7	—	—	—	585	0.42	1.7	45	0.25	1.4	—	—	—
	T8430	0.8	210	0.35	1.7	115	0.32	1.7	—	—	—	585	0.42	1.7	45	0.25	1.4	—	—	—
	T9325	0.8	255	0.35	1.7	150	0.32	1.7	—	—	—	—	—	—	55	0.25	1.4	—	—	—
WNMG 080412EL-SI	T8430	1.2	225	0.35	1.7	120	0.32	1.7	—	—	—	615	0.42	1.7	45	0.25	1.4	—	—	—




W-F wiper geometry for fine to finish machining with increased feed rates and improved surface finish.

WNMG 060408W-F	T9315	0.8	215	0.45	0.8	—	—	—	200	0.45	0.8	—	—	—	—	—	—	—	—	—
	T9325	0.8	190	0.45	0.8	—	—	—	180	0.45	0.8	—	—	—	—	—	—	—	—	—
WNMG 080404W-F	T9315	0.4	250	0.25	0.4	—	—	—	235	0.25	0.4	—	—	—	—	—	—	—	—	—
	T9325	0.4	225	0.25	0.4	—	—	—	210	0.25	0.4	—	—	—	—	—	—	—	—	—




W-M wiper geometry for semi-rough to rough machining with increased feed rates and improved surface finish.

WNMG 060408W-M	T9310	0.8	220	0.45	1.2	—	—	—	205	0.45	1.2	—	—	—	—	—	—	—	—	—
	T9315	0.8	205	0.45	1.2	—	—	—	190	0.45	1.2	—	—	—	—	—	—	—	—	—
	T9325	0.8	190	0.45	1.2	—	—	—	180	0.45	1.2	—	—	—	—	—	—	—	—	—
WNMG 060412W-M	T5315	1.2	235	0.55	1.2	—	—	—	220	0.55	1.2	—	—	—	—	—	—	—	—	—
	T9315	1.2	205	0.55	1.2	—	—	—	190	0.55	1.2	—	—	—	—	—	—	—	—	—
	T9325	1.2	180	0.55	1.2	—	—	—	170	0.55	1.2	—	—	—	—	—	—	—	—	—
WNMG 080408W-M	T9315	0.8	200	0.45	1.5	—	—	—	190	0.45	1.5	—	—	—	—	—	—	—	—	—
	T9325	0.8	185	0.45	1.5	—	—	—	175	0.45	1.5	—	—	—	—	—	—	—	—	—
WNMG 080412W-M	T9325	1.2	180	0.55	1.5	—	—	—	170	0.55	1.5	—	—	—	—	—	—	—	—	—



W-MR wiper geometry for finish to rough machining with increased feed rates and improved surface finish.

WNMG 060408W-MR	T9315	0.8	205	0.45	1.2	—	—	—	190	0.45	1.2	—	—	—	—	—	—	—	—	—
	T9325	0.8	190	0.45	1.2	110	0.41	1.2	180	0.45	1.2	—	—	—	—	—	—	—	—	—
WNMG 080404W-MR	T9315	0.4	200	0.30	1.5	—	—	—	190	0.30	1.5	—	—	—	—	—	—	—	—	—
	T9325	0.4	180	0.30	1.5	105	0.27	1.5	170	0.30	1.5	—	—	—	—	—	—	—	—	—
WNMG 080408W-MR	T5315	0.8	230	0.45	1.5	—	—	—	215	0.45	1.5	—	—	—	—	—	—	—	—	—
	T9310	0.8	215	0.45	1.5	—	—	—	200	0.45	1.5	—	—	—	—	—	—	—	—	—
	T9315	0.8	200	0.45	1.5	—	—	—	190	0.45	1.5	—	—	—	—	—	—	—	—	—
	T9325	0.8	185	0.45	1.5	110	0.41	1.5	175	0.45	1.5	—	—	—	—	—	—	—	—	—
WNMG 080412W-MR	T5315	1.2	230	0.55	1.5	—	—	—	215	0.55	1.5	—	—	—	—	—	—	—	—	—
	T9310	1.2	210	0.55	1.5	—	—	—	195	0.55	1.5	—	—	—	—	—	—	—	—	—
	T9315	1.2	200	0.55	1.5	—	—	—	190	0.55	1.5	—	—	—	—	—	—	—	—	—
	T9325	1.2	180	0.55	1.5	105	0.50	1.5	170	0.55	1.5	—	—	—	—	—	—	—	—	—




W-NM wiper geometry for finish to rough machining with increased feed rates and improved surface finish.

WNMG 060408W-NM	T7325	0.8	220	0.25	1.8	170	0.23	1.8	—	—	—	—	—	—	70	0.20	1.4	—	—	—
	T7335	0.8	215	0.25	1.8	165	0.23	1.8	—	—	—	—	—	—	65	0.20	1.4	—	—	—
	T9315	0.8	290	0.25	1.8	—	—	—	275	0.25	1.8	—	—	—	—	—	—	—	—	—
	T9325	0.8	265	0.25	1.8	155	0.23	1.8	250	0.25	1.8	—	—	—	55	0.20	1.4	—	—	—



Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE [mm]	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]




W-NM wiper geometry for finish to rough machining with increased feed rates and improved surface finish.

WNMG 080404W-NM	T7325	0.4	195	0.20	2.1	150	0.18	2.1	—	—	—	—	—	—	60	0.16	1.7	—	—	—
	T7335	0.4	190	0.20	2.1	145	0.18	2.1	—	—	—	—	—	—	60	0.16	1.7	—	—	—
	T9315	0.4	270	0.20	2.1	—	—	—	255	0.20	2.1	—	—	—	—	—	—	—	—	—
	T9325	0.4	240	0.20	2.1	140	0.18	2.1	225	0.20	2.1	—	—	—	50	0.16	1.7	—	—	—
WNMG 080408W-NM	T7325	0.8	215	0.25	2.1	165	0.23	2.1	—	—	—	—	—	—	65	0.20	1.7	—	—	—
	T7335	0.8	210	0.25	2.1	160	0.23	2.1	—	—	—	—	—	—	65	0.20	1.7	—	—	—
	T9315	0.8	290	0.25	2.1	—	—	—	275	0.25	2.1	—	—	—	—	—	—	—	—	—
	T9325	0.8	260	0.25	2.1	155	0.23	2.1	245	0.25	2.1	—	—	—	55	0.20	1.7	—	—	—
WNMG 080412W-NM	T7325	1.2	215	0.30	2.1	165	0.27	2.1	—	—	—	—	—	—	65	0.24	1.7	—	—	—
	T7335	1.2	210	0.30	2.1	160	0.27	2.1	—	—	—	—	—	—	65	0.24	1.7	—	—	—
	T9315	1.2	285	0.30	2.1	—	—	—	270	0.30	2.1	—	—	—	—	—	—	—	—	—

WNMM




	IC [mm]	D1 [mm]	L [mm]	S [mm]
0804	12.700	5.16	8.70	4.76
1006	15.875	6.35	10.80	6.35
1306	19.050	7.94	13.00	6.35




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE [mm]	P			M			K			N			S			H		
			vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap	vc	f	ap
			[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]	[m/min]	[mm/rev]	[mm]




DR geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMM 100608E-DR	T9325	0.8	205	0.40	5.0	120	0.36	5.0	190	0.40	5.0	—	—	—	—	—	—	—	—	—
	T9335	0.8	175	0.40	5.0	105	0.36	5.0	—	—	—	—	—	—	—	—	—	—	—	—
WNMM 130612E-DR	T9325	1.2	200	0.45	6.0	120	0.41	6.0	190	0.45	6.0	—	—	—	—	—	—	—	—	—
	T9335	1.2	170	0.45	6.0	100	0.41	6.0	—	—	—	—	—	—	—	—	—	—	—	—



NR geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMM 080408E-NR	T7325	0.8	175	0.40	3.0	135	0.36	3.0	—	—	—	—	—	—	55	0.28	2.4	—	—	—
	T8330	0.8	155	0.40	3.0	90	0.36	3.0	145	0.40	3.0	—	—	—	35	0.28	2.4	—	—	—
	T8430	0.8	165	0.40	3.0	90	0.36	3.0	135	0.40	3.0	—	—	—	35	0.28	2.4	—	—	—
	T9325	0.8	195	0.40	3.0	115	0.36	3.0	185	0.40	3.0	—	—	—	40	0.28	2.4	—	—	—





NR2 geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMM 080408E-NR2	T7335	0.8	160	0.40	4.0	120	0.36	4.0	—	—	—	—	—	—	50	0.28	3.2	—	—	—
	T9325	0.8	190	0.40	4.0	110	0.36	4.0	180	0.40	4.0	—	—	—	40	0.28	3.2	—	—	—




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE [mm]	P			M			K			N			S			H		
			vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]



NR2 geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMM 080412E-NR2	T7325	1.2	175	0.45	4.0	135	0.41	4.0	—	—	—	—	—	—	55	0.32	3.2	—	—	—
	T9325	1.2	190	0.45	4.0	110	0.41	4.0	180	0.45	4.0	—	—	—	40	0.32	3.2	—	—	—




OR geometry for semi-rough to rough machining, and continuous to interrupted cuts.

WNMM 080408E-OR	T8330	0.8	150	0.40	4.0	90	0.36	4.0	140	0.40	4.0	—	—	—	35	0.28	3.2	—	—	—
	T8430	0.8	155	0.40	4.0	85	0.36	4.0	130	0.40	4.0	—	—	—	30	0.28	3.2	—	—	—
	T9325	0.8	190	0.40	4.0	110	0.36	4.0	180	0.40	4.0	—	—	—	40	0.28	3.2	—	—	—
	T9335	0.8	165	0.40	4.0	95	0.36	4.0	—	—	—	—	—	—	35	0.28	3.2	—	—	—
WNMM 080412E-OR	T9325	1.2	190	0.45	4.0	110	0.41	4.0	180	0.45	4.0	—	—	—	40	0.36	3.2	—	—	—
	T9335	1.2	170	0.45	4.0	100	0.41	4.0	—	—	—	—	—	—	35	0.36	3.2	—	—	—
WNMM 080416E-OR	T9325	1.6	195	0.50	4.0	115	0.45	4.0	185	0.50	4.0	—	—	—	40	0.40	3.2	—	—	—
WNMM 130612E-OR	T9325	1.2	185	0.45	6.0	110	0.41	6.0	175	0.45	6.0	—	—	—	40	0.36	4.8	—	—	—
WNMM 130616E-OR	T9325	1.6	180	0.50	6.0	105	0.45	6.0	170	0.50	6.0	—	—	—	40	0.40	4.8	—	—	—

WNGA CBN




	IC [mm]	D1 [mm]	L [mm]	S [mm]
0804	12.700	5.16	8.70	4.76




Suitability and starting values for cutting speed (vc), feed (f) and depth of cut (ap). Refer to our Machining Calculator app for further calculations.

Product		RE [mm]	P			M			K			N			S			H		
			vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]	vc [m/min]	f [mm/rev]	ap [mm]



For finish machining and continuous cuts.

WNGA 080408S01020C	TB310	0.8	—	—	—	—	—	—	530	0.15	0.6	—	—	—	140	0.11	0.5	110	0.15	1.0
--------------------	-------	-----	---	---	---	---	---	---	-----	------	-----	---	---	---	-----	------	-----	-----	------	-----



For finish machining and continuous cuts.

WNGA080408S01020WC	TB310	0.8	—	—	—	—	—	—	530	0.15	0.6	—	—	—	140	0.11	0.5	110	0.15	1.0
--------------------	-------	-----	---	---	---	---	---	---	-----	------	-----	---	---	---	-----	------	-----	-----	------	-----